

NOS Multi Injection unit

Specification

NOS

NOS HP6505-25, Multi injection unit are the latest in our HP6505 range of units for chemical injections. The unit compacts 4 separate injection units into one unit. Allowing up to 4 different chemical injection simultaneously. Efficient and easy to use injection pumps made for use in ATEX zone 1 areas.



Multi Injection Unit			
Approvals		DNV 2.71, Norsok Z-015	
Area Classification		ATEX Sone 1	
Frame Envelope Size		2000 x 2000 x 2000mm (LxWxH)	
M.G.W		6600 kg	
Tare		4500 kg	
Max Payload		2100 kg	
Z-015 Type		U10	
Ambient Operating temperature		0 – 60 °C (below 0°C contact NOS)	
Tanks & Supply			
Tank size		4x 80ltr	
Inlet All tanks		¾" JIC w/ float valve	
Supply pumps		Yamada NDP15	
Max Pressure		7 bar	
Max Flow		250 ltr/min	
Pumps - Williams Metering Pump			
Unit	Pump	Pressure	Flow
Unit 1	P2250W600	69 bar	160ml – 5,6ltr/ min
Unit 2	P1500W800	221 bar	36ml – 1,4ltr/ min
Unit 3	P1000W800	349 bar	12,3ml – 0,55ltr/min
Unit 4	P500W400	224 bar	3,2ml – 0,145ltr/min
Supply / connections			
Air supply		1" Chicago claw	
Outlet Unit 1		½" JIC M	
Outlet Unit 2		½" JIC M	
Outlet Unit 3		½" JIC M	
Outlet Unit 4		¼" JIC M	

NOS Rental (NOS)
 Forusbeen 226
 4313 Sandnes
 Tlf: 51733000

nosas.no